# SAFETY DATA SHEET SUPERIOR No. 88-13-8975

DATE REVISED: January 1, 2017

**Product Name:** Superior No. 88-13-8975

Manufacturer: Superior Flux & Mfg. Co. 6615 Parkland Blvd. Cleveland, OH 44139

**Emergency Phone Number: 1-800-424-9300 (CHEMTREC)** 

Other Information Calls: (440) 349-3000

**To the Purchaser:** This MSDS contains important environmental, health, and toxicology information for your employees who have ordered this product. Please be sure this information is given to them. If you resell this product, a copy of the MSDS should be given to the buyer.

H.M.I.S. INFORMATION: HEALTH = 1 FLAMMABILITY = 1 REACTIVITY = 1

## **SECTION I - IDENTIFICATION**

**Common Name:** Superior No. 88-13-8975 **Chemical Family:** Water Soluble Solder Paste

CAS Number: NA Chemical Name: NA Formula: See Below

# SECTION II – HAZARDS IDENTIFICATION

Classification of Substance or Mixture:

Classification (CLP): No Data Available Label Elements (CLP): No Data Available





Warning Health hazard **H Statements:** H334, H317 **P Statements:** P280, P302+P352

Risk Phrases: None

Safety Phrases: S36, S39

See section XVI for full text description of S and R phrases

**Other Hazards:** None if used properly

## SECTION III- COMPOSITION INFORMATION

Components	CAS Number	%	OSHA PEL
Tin	7440-31-5	70-80	$2.00 \text{ mg/m}^3$
Lead	7439921	30-40	$0.15 \text{ mg/m}^3$

Unlisted percentages are non-hazardous stabilizers, activators, and water. None of the materials in this product are listed in NTP, IARC, or OSHA as carcinogens.

## SECTION IV- HEALTH HAZARDS

**Primary Routes of Entry:** Fume inhalation, ingestion, skin, and eyes.

**Signs and Symptoms of Exposure:** 

1) Acute Effects: Reddening of eyes and skin, acid stomach if ingested, inhalation may cause

respiratory tract irritation.

2) Chronic Effects: No specific information available

Medical Conditions Generally Aggravated by Overexposure: None presently known.

Chemical Listed as a Carcinogen or Potential Carcinogen: None

**OSHA Permissible Exposure Limit (PEL):** 0.15 mg/m<sup>3</sup> **ACGIH Threshold Limit Value (TLV):** 0.15 mg/m<sup>3</sup>

## **EMERGENCY AND FIRST AID PROCEDURES**

**Eyes:** Flush with water for 10 minutes. Call a physician.

**Skin:** Wash thoroughly with water.

**Inhalation:** Remove to fresh air or administer oxygen. Call a physician.

**Ingestion:** If patient is fully conscious, give two glasses of water. Obtain medical attention

immediately.

## SECTION V - FIRE AND EXPLOSION HAZARD DATA

Flash Point: Core>140°C

Metal: NA

Flammable Limits: NA

Extinguishing Media: Special mixtures of dry chemicals suitable for metal fires such as dry sand,

dolomite, graphite, salt, and soda ash.

Do Not Apply Water to Burning or Melted Metal. Water can be used to cool containers when no

contact with metal will occur. **Auto Ignition Temperature:** NA

#### SECTION VI - ACCIDENTAL RELEASE MEASURES

**Steps to be taken in case material is spilled:** Protect skin and eyes by wearing safety glasses and gloves. Ventilate the area. Restrict and collect spilled materials

#### SECTION VII - HANDLING AND STORAGE

**Storage Requirements:** Store in low temperature and low humidity area.

**Handling Precautions:** Users should wear protective gloves and glasses when handling solder paste.

soldering should be conducted in good ventilation environment.

Other Precautions: Keep the tin, silver, and lead fume levels below the OSHA permissible exposure

limit.

#### SECTION VIII - CONTROL MEASURES

**Respiratory Protection (TYPE):** NIOSH approved.

Ventilation: Yes

Mechanical (General): Optional

**Local Exhaust:** Yes

**Eye Protection:** Safety glasses **Protective Gloves:** Rubber gloves

Other Protective Clothing or Equipment: Laboratory or worker coat

Work/Hygienic Practices: Wash hands after handling the product, wear safety glasses during handling

## SECTION IX - PHYSICAL AND CHEMICAL CHARACTERISTICS

**Boiling Point:** NA

Specific Gravity (Water = 1): 4.0-5.5 Vapor Pressure (mm Hg): NA Percent Volatile by Volume: NA

**Vapor Density (Air = 1):** NA

**Evaporation Rate (Butyl Acetate = 1):** NA

Melting Point: 183°C Solubility in Water: Partial Reactivity in Water: None

Appearance and Odor: Pasty and mild solvent odor

#### SECTION X - STABILITY AND REACTIVITY

**Stability:** Product is stable

(Conditions to Avoid): Contact with strong acids and alkali.

**Incompatibility:** Strong acids and alkali.

**Hazardous Decomposition Products:** Not determined.

**Hazardous Polymerization:** Not determined. **(Conditions to Avoid):** Not determined

## SECTION XI - TOXICOLOGICAL INFORMATION

## **Acute Toxicity Data**

1) Oral: LD-50 (rat): Not available

2) Inhalation: LC-50 (rat): Not available
3) Dermal: LD-50 (rabbit): Not available
4) Skin Irritation: (rabbit): Not available

#### **Chronic Toxicity Data**

1) Repeated Skin Application: (rat): Not available

2) Eye Irritation: (rabbit): Not available

#### SECTION XII - ECOLOGICAL INFORMATION

This Material has not been Tested for Environmental Effects.

#### SECTION XIII - DISPOSAL CONSIDERATIONS

**Waste Disposal Method:** Dispose of in accordance with EPA regulations.

#### SECTION XIV- TRANSPORTATION

**D.O.T. Proper Shipping Name:** Non-hazardous

Identification Number:NAHazard Class:NAType D.O.T Label Required Information:NAPacking Group:NA

#### SECTION XV - REGULATORY INFORMATION

OSHA Hazardous Chemical According to 29 CFR 1910.1200: None

Carcinogenicity Classification (Components Present at 0.1% or More): Non-Carcinogenic

International Agency for Research on Cancer (IARC): Not Listed

American Conference of Governmental Industrial Hygienists (ACGIH): Not Listed

National Toxicology Program (NTP): Not Listed

Occupational Safety and Health Administration (OSHA): Not Listed

None of the Components of this Product are Listed on the U.S. Toxic Substances Control Act. Inventory or Otherwise Comply with TSCA Pre-manufacture Notification Requirements. This Product is RoHS Compliant.

## **SECTION XVI - OTHER INFORMATION**

The labeling of this product is indicated in Section II. The full text of all abbreviations indicated by codes in the MSDS are as follows:

S-36/39	Wear suitable protective clothing and eye/face protection
H334 H317	May cause allergy or asthma symptoms or breathing difficulties if inhaled May cause an allergic skin reaction
P280 P302+P352	Wear protective gloves/protective clothing/eye protection/face protection IF ON SKIN: Wash with plenty of water and soap.

**Disclaimer:** Judgments as to the suitability of information herein or the purchaser's purposes are necessarily the purchaser's responsibility. Reasonable care has been taken in the preparation of this material, but there are NO WARRANTIES, NO REPRESENTATIONS AND NO RESPONSIBILITY AS TO THE ACCURACY OR THE SUITABILITY OF THIS INFORMATION FOR ANY PURCHASER'S USE OR FOR ANY CONSEQUENCE TO USE.