SAFETY DATA SHEET SUPERIOR No. 1260

DATE REVISED: January 1, 2016

Product Name: Superior No. 1260

Manufacturer: Superior Flux & Mfg. Co. 6615 Parkland Blvd. Cleveland, OH 44139 Emergency Phone Number: 1-800-424-9300 (CHEMTREC) Other Information Calls: (440) 349-3000

To the Purchaser: This MSDS contains important environmental, health, and toxicology information for your employees who have ordered this product. Please be sure this information is given to them. If you resell this product, a copy of the MSDS should be given to the buyer.

H.M.I.S. INFORMATION: HEALTH = 2 FLAMMABILITY = 1 REACTIVITY = 1

SECTION I – IDENTIFICATION

Common Name: Superior No. 1260 Relevant Identified Uses: Soldering Flux for Aluminum Chemical Family: Aluminum paste flux CAS Number: NA Chemical Name: NA Formula: See below

SECTION II – HAZARDS IDENTIFICATION

Classification of Substance or Mixture:

Classification (CLP): No Data Available **Label Elements (CLP):** C – Corrosive



Risk Phrases: R61, R62, R34, R43, R36/37/38, R50/53 **Safety Phrases:** S-26, S-36/37/39, S-45 See section XVI for full text description of S and R phrases **Other Hazards:** None if used properly

SECTION III- COMPOSITION INFORMATION

Components Aminoethylethanolami	CAS Number ne 111-41-1	EC No. 203-867-5	% 20-29	OSHA PEL NA	Classifications (1272/2008) H360Fd, H361, H314, H317, H335	Classification(1999/45) T R61/34/43/62 C R34, C≥10% Xi, R36/37/38
Ammonium Fluoborate	13826-83-0	237-531-4	15-29	2.5 mg/m^3	H302, H312, H332, H319	Xn-R22, Xi-R36/37/38
Zinc Oxide	1314-13-2	215-222-5	5-15	5.0 mg/m^3	H400-Acute 1, H410-Chronic 2	N-R50/53
Triethanolamine	102-71-6	203-049-8	20-29	NĂ	NA	Xi-R36/38

Unlisted percentages are non-hazardous stabilizers, and water. None of the materials in this product are listed in NTP, IARC, or OSHA as carcinogens. See section XVI for full text description of S and R phrases, H statements, and classification.

SECTION IV - FIRST AID MEASURES

Description of First Aid Measures

Eyes:	Flush with water for 15 minutes. Call a physician.			
Skin:	Wash thoroughly with soap and water. If rash develops call a physician.			
Inhalation:	Remove to fresh air or administer oxygen. Call physician.			
Ingestion:	Get medical attention immediately.			

Most Important Symptoms and effects, both acute and delayed

Primary Routes of Entry: Fume inhalation, ingestion, skin, and eyes.
Symptoms of Overexposure: Eye and skin burns, damage to digestive and respiratory system, abdominal pain, vomiting and effects central nervous system.
Medical Conditions Generally Aggravated by Overexposure: Lung and skin disorders.
Chemical Listed as a Carcinogen or Potential Carcinogen: None
OSHA Permissible Exposure Limit (PEL): 2.5 mg/m³
ACGIH Threshold Limit Value (TLV): 2.5 mg/m³

SECTION V - FIRE AND EXPLOSION HAZARD DATA

Flash Point: >135 C/275°F
Flammable Limits: Lower-1.5, Upper-10.0
Extinguishing Media: Water, fog, foam or dry chemical
Auto Ignition Temperature: None
Special Fire Fighting Procedures: Full protective equipment required. ammonia, boron oxide, or fluoride fumes may be released.
Unusual Fire and Explosion Hazards: Decomposition may produce NO₂ fumes. Hydrofluoric acid solution may be formed within water run-off.

SECTION VI - ACCIDENTAL RELEASE MEASURES

Steps to be taken in case material is spilled: Contain, absorb, sweep-up and dispose.

SECTION VII - HANDLING AND STORAGE

Storage Requirements: Store in plastic containers in cool area, away from heat. **Handling Precautions:** Wash hands thoroughly after handling. Safe precautionary practices to avoid spills and exposure to skin and fumes.

SECTION VIII - CONTROL MEASURES

Respiratory Protection (Type): NIOSH approved respirator in absence of adequate ventilation. Ventilation: Yes Mechanical (General): Yes Local Exhaust: Yes Eye Protection: Safety goggles Protective Gloves: NIOSH approved chemical resistant Other Protective Clothing or Equipment: Full protective clothing to prevent any contact.

SECTION IX - PHYSICAL AND CHEMICAL CHARACTERISTICS

Boiling Point: NA Specific Gravity: 1.32 Vapor Pressure (mm Hg): NA Percent Volatile by Volume: NA VOC: <5% Vapor Density (Air = 1): NA Evaporation Rate (Butyl Acetate = 1): N/A Melting Point: NA Solubility in Water: Freely soluble Reactivity in Water: NA Appearance and Odor: Amber gel with ammonia odor

SECTION X - STABILITY AND REACTIVITY

Stability: Product is stable
(Conditions to Avoid): Excess heat
Incompatibility: Strong oxidants, sulfides and cyanides.
Hazardous Decomposition Products: Hydrofluoric acid, ammonia, NO₂, boron tri-fluoride gases.
Hazardous Polymerization: Will not occur
(Conditions to Avoid): NA

SECTION XI - TOXICOLOGICAL INFORMATION

Acute Toxicity Data

- 1) Oral: LD-50 (rat): Not available
- 2) Inhalation: LC-50 (rat): Not available
- **3) Dermal:** LD-50 (rabbit): Not available
- 4) Skin Irritation: (rabbit): Not available

Chronic Toxicity Data

- 1) Repeated Skin Application: (rat): Not available
- 2) Eye Irritation: (rabbit): Not available

SECTION XII - ECOLOGICAL INFORMATION

This material has not been tested for environmental effects.

SECTION XIII - DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose of in accordance with EPA regulations

SECTION XIV- TRANSPORTATION

D.O.T. Proper Shipping Name: Corrosive liquid, N.O.S (contains aminoethylethanolamine, ammonium fluoborate)
Hazard Class: 8
Identification Number: UN1760
Packing Group: II
Type D.O.T Label Required Information: Corrosive
Waste Disposal Method: Dispose of in accordance with EPA regulations

SECTION XV - REGULATORY INFORMATION

OSHA Hazardous Chemical According to 29 CFR 1910.1200: NA Carcinogenicity Classification: (Components Present at 0.1% or More) International Agency for Research on Cancer (IARC): NA American Conference of Governmental Industrial Hygienists (ACGIH): NA National Toxicology Program (NTP): NA Occupational Safety and Health Administration (OSHA): NA All Components of this Product are Listed on the U.S. Toxic Substances Control Act Inventory or Otherwise Comply with TSCA Pre-manufacture Notification Requirements. This Product is RoHS and REACH Compliant.

SECTION XVI - OTHER INFORMATION

The labeling of this product is indicated in Section II. The full text of all abbreviations indicated by codes in the MSDS are as follows:

Xi	Irritant				
Xn	Harmful				
R22	Harmful if swallowed				
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment				
R61	May cause harm to unborn child				
R62	Possible risk to fertility				
R34	Causes burns				
R43	May cause sensitization by skin contact				
R36	Irritating to eyes				
R37	Irritating to respiratory system				
R38	Irritating to skin				
S-26	In case of eye contact, rinse thoroughly and get medical attention				
S-36/37/39	Wear suitable protective clothing, gloves, and eye/face protection				
S-45	In case of accident or if you feel unwell seek medical advisement immediately				
H227	Combustible Liquid				
H301 + H311	Toxic if swallowed, toxic if contact with skin				
H302	Harmful if swallowed				
H312	Harmful if contact with skin				
H360Fd	May damage unborn child, suspected of damage to fertility				
H314	Causes severe burns and eye damage				
H317	May cause allergic skin reaction				
H335	May cause respiratory irritation				
H332	Harmful if inhaled				
H319	Causes eye irritation				
H373	May cause damage to organs through prolonged or repeated exposure				
H400	Very toxic to aquatic life				
H410	Very toxic to aquatic life, with long lasting effects				

Further information:

Judgments as to the suitability of information herein or the purchaser's purposes are necessarily the purchaser's responsibility. Reasonable care has been taken in the preparation of this material, but there are NO MSDS. Superior No. 1260. Page 4 of 5

WARRANTIES, NO REPRESENTATIONS AND NO RESPONSIBILITY AS TO THE ACCURACY OR THE SUITABILITY OF THIS INFORMATION FOR ANY PURCHASER'S USE OR FOR ANY CONSEQUENCE TO USE.