SAFETY DATA SHEET SUPERIOR NO. 75

DATE REVISED: January 1, 2016

Product Name: Superior No. Superior 75

Manufacturer: Superior Flux & Mfg. Co. 6615 Parkland Blvd. Cleveland, OH 44139

Emergency Phone Number: 1-800-424-9300 (CHEMTREC)

Other Information Calls: (440) 349-3000

To the Purchaser: This MSDS contains important environmental, health, and toxicology information for your employees who have ordered this product. Please be sure this information is given to them. If you resell this product, a copy of the MSDS should be given to the buyer.

H.M.I.S. INFORMATION: HEALTH = 3 FLAMMABILITY = 0 REACTIVITY = 0

SECTION I - IDENTIFICATION

Common Name: Superior 75

Chemical Family: Soft Soldering Flux

CAS Number: NA Chemical Name: NA Formula: See below

SECTION II – HAZARDS IDENTIFICATION

Classification of Substance or Mixture:

Classification (CLP): Corrosive Label Elements (CLP): Corrosive







Corrosive

Irritant Environmentally Damaging

Precautionary Phrases: P264, P270, P273, P280, P301+P312, P305+P351+P338, P330, P337+P313,

P301+P330+P331, P304+P340, P309+P311

Risk Phrases: R36/37/38, R34

Safety Phrases: S-26, S-27, S-36/37/39, S-45, S18, S61, S62, S64

See section XVI for full text description of S and R phrases

Other Hazards: None if used properly

SECTION III- COMPOSITION INFORMATION

Components	CAS Number	%	OSHA PEL	H Phrases
Ammonium Chloride Hydrochloric Acid Zinc Chloride	12125-02-9 7647-01-0 7646-85-7	4-15 3-10 30-45	NA 5 mg/m ³ 1 mg/m ³	H302, H319, H401 H314, H335 H302, H314, H319, H335, H400, H401

Unlisted percentages are non-hazardous stabilizers, and water. None of the materials in this product are listed in NTP, IARC, or OSHA as carcinogens.

SECTION IV – FIRST AID MEASURES

Inhalation: Remove to fresh air

Eyes: Flush with water for fifteen (15) Minutes. Call physician.

Skin: Wash thoroughly with soap and water.

Ingestion: If patient is fully conscious, give large amounts of water. Obtain medical attention

immediately.

Most Important Symptoms and effects, both acute and delayed

Primary Routes of Entry into Body: Fume inhalation, ingestion, skin, and eyes.

Symptoms of Overexposure: Salivation, coughing, choking, chills, may cause weight loss, brittle

bones, anemia, and stiff joints.

Medical Conditions Generally Aggravated by Exposure: Any weakness of the lungs, kidneys or

liver will be aggravated.

Chemical Listed as Carcinogen or Potential Carcinogen: None

OSHA Permissible Exposure Limit (PEL): NA **ACGIH Threshold Limit Value (TLV):** NA

SECTION V - FIRE AND EXPLOSION HAZARD DATA

Flash Point: NA

Flammable Limits: NA

Extinguishing Media: Dry chemical, CO₂ foam

Auto Ignition Temperature: None

Special Fire Fighting Procedures: Normal cautions when dealing with chemicals.

Unusual Fire and Explosion Hazards: Will release small amounts of HCl upon decomposition

SECTION VI - ACCIDENTAL RELEASE MEASURES

Steps to be Taken in Case Material is Spilled: First neutralize with soda ash or sodium bicarbonate, dilute with water and dispose of in accordance with EPA regulations.

SECTION VII - HANDLING AND STORAGE

Storage Requirements: Store in plastic containers in cool area, away from heat.

Handling Precautions: Safe precautionary practices to avoid spills and exposure to skin and fumes.

Other Precautions: NA

SECTION VIII - CONTROL MEASURES

Respiratory Protection (TYPE): NIOSH approved respirator.

Ventilation: Yes

Mechanical (General): Explosion proof

Local Exhaust: Yes

Protective Gloves: Recommended, NIOSH approved

Other Protective Clothing or Equipment: Rubber apron is recommended.

Eye Protection: Safety Glasses

Regulatory Information: The chemical components are listed on TSCA and DSL inventory. See

composition section ii for CAS numbers

SECTION IX - PHYSICAL AND CHEMICAL CHARACTERISTICS

Boiling Point: 104°C/220°F

Specific Gravity (Water = 1): 1.32 Vapor Pressure (mm Hg): NA

VOC Content: 0%

pH: 0-1.00

Vapor Density (Air = 1): NA

Evaporation Rate (Butyl Acetate = 1): 0.6

Melting Point: 0°C/32°F

Solubility in Water: Unlimited **Reactivity in Water:** None

Appearance and Odor: Clear odorless liquid

SECTION X - STABILITY AND REACTIVITY

Stability: Product is stable (Conditions to Avoid): Metals

Incompatibility: Alkaline, strong oxidizing or reducing materials, cyanides or combustible materials.

Hazardous Decomposition Products: HCl, zinc chloride, zinc oxide, ammonium.

Hazardous Polymerization: Will not occur (Conditions to Avoid): Excessive heat or cold

SECTION XI - TOXICOLOGICAL INFORMATION

Acute Toxicity Data

1) Oral: LD-50 (rat): Not available

2) Inhalation: LC-50 (rat): Not available3) Dermal: LD-50 (rabbit): Not available

4) Skin Irritation: (rabbit): Not available

Chronic Toxicity Data

1) Repeated Skin Application: (rat): Not available

2) Eye Irritation: (rabbit): Not available

SECTION XII - ECOLOGICAL INFORMATION

This material has not been tested for environmental effects.

SECTION XIII - DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose of in accordance with EPA regulations

SECTION XIV- TRANSPORTATION

D.O.T. Proper Shipping Name: Corrosive Liquid, Acidic, Inorganic, N.O.S.

(Contains Zinc Chloride, Hydrochloric Acid)

Hazard Class: 8

Identification Number: UN3264

Packing Group: III

Type D.O.T Label Required Information: Corrosive

SECTION XV - REGULATORY INFORMATION

OSHA Hazardous Chemical According to 29 CFR 1910.1200: NA

Carcinogenicity Classification: (Components Present at 0.1% or More)

International Agency for Research on Cancer (IARC): NA

American Conference of Governmental Industrial Hygienists (ACGIH): NA

National Toxicology Program (NTP): NA

Occupational Safety and Health Administration (OSHA): NA

All Components of this Product are Listed on the U.S. Toxic Substances Control Act Inventory or Otherwise Comply with TSCA. Dre manufacture Notification Requirements

Otherwise Comply with TSCA Pre-manufacture Notification Requirements.

This product is RoHS compliant.

SECTION XVI - OTHER INFORMATION

The labeling of this product is indicated in Section II. The full text of all abbreviations indicated by codes in the MSDS are as follows:

R34 R36 R37 R38	Causes burns Irritating to eyes Irritating to respiratory system Irritating to skin	
S-18	Handle and open container with care	
S-26	In case of eye contact, rinse thoroughly and get medical attention	
S-27	Take off immediately contaminated clothing	
S-36/37/39	Wear suitable protective clothing, gloves, and eye/face protection	
S-45	In case of accident or if feel unwell call medical advice immediately	
S61	Avoid release to the environment. Refer to special instructions/safety data sheet	
S62	If swallowed, do not induce vomiting: seek medical advice immediately and show	
	this container or label where possible	
S64	If swallowed, rinse mouth with water (only if the person is conscious)	
P264	Wash thoroughly after handling	
P270	Do not eat, drink or smoke when using this product	
P273	Avoid release to the environment	
P280	Wear protective gloves/protective clothing/eye protection/face protection	
P301+P312	IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel	
unwell		
P305+P351+	•	
P330	contact lenses if present and easy to do – continue rinsing Rinse mouth	
P337+P313		
P337+P313 If eye irritation persists get medical advice/attention P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting		
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position	
1 307 11 370	comfortable for breathing	
P309+P311	IF exposed or you feel unwell: Call a POISON CENTER or doctor/physician	

H302	Harmful if swallowed
H319	Causes serious eye irritation
H401	Toxic to aquatic life
H314	Causes severe skin burns and eye damage
H335	May cause respiratory irritation
H400	Very toxic to aquatic life

Further information:

Judgments as to the suitability of information herein or the purchaser's purposes are necessarily the purchaser's responsibility. Reasonable care has been taken in the preparation of this material, but there are NO WARRANTIES, NO REPRESENTATIONS AND NO RESPONSIBILITY AS TO THE ACCURACY OR THE SUITABILITY OF THIS INFORMATION FOR ANY PURCHASER'S USE OR FOR ANY CONSEQUENCE TO USE.