# SAFETY DATA SHEET SUPERIOR No. 592-64-8825

DATE REVISED: January 1, 2017

#### Product Name: Superior No. 592-64-8825

Manufacturer: Superior Flux & Mfg. Co. 6615 Parkland Blvd. Cleveland, OH 44139 Emergency Phone Number: 1-800-424-9300 (CHEMTREC) Other Information Calls: (440) 349-3000

**To the Purchaser**: This MSDS contains important environmental, health, and toxicology information for your employees who have ordered this product. Please be sure this information is given to them. If you resell this product, a copy of the MSDS should be given to the buyer.

#### H.M.I.S. INFORMATION: HEALTH = 1 FLAMMABILITY = 1 REACTIVITY = 1

## **SECTION I - IDENTIFICATION**

Common Name: Superior No. 592-64-8825 Chemical Family: Water Soluble Dispensable Solder Paste CAS Number: NA Chemical Name: NA Formula: See Below

# SECTION II – HAZARDS IDENTIFICATION

Classification of Substance or Mixture:

Classification (CLP): No Data Available Label Elements (CLP): No Data Available



Warning Health hazard H Statements: H334, H317 P Statements: P280, P302+P352 Risk Phrases: None Safety Phrases: S36, S39 See section XVI for full text description of S and R phrases Other Hazards: None if used properly

## SECTION III- COMPOSITION INFORMATION

Components	CAS Number	%	<b>OSHA PEL</b>
Tin	7440-31-5	70-99	$2.00 \text{ mg/m}^3$
Silver	7440-22-4	2-10	$0.10 \text{ mg/m}^3$

Unlisted percentages are non-hazardous stabilizers, activators, and water. None of the materials in this product are listed in NTP, IARC, or OSHA as carcinogens.

# SECTION IV- HEALTH HAZARDS

Primary Routes of Entry: Fume inhalation, ingestion, skin, and eyes.

- Signs and Symptoms of Exposure:
  - 1) Acute Effects: Reddening of eyes and skin, acid stomach if ingested, inhalation may cause respiratory tract irritation.
  - 2) Chronic Effects: No specific information available

Medical Conditions Generally Aggravated by Overexposure: None presently known.

Chemical Listed as a Carcinogen or Potential Carcinogen: None

**OSHA Permissible Exposure Limit (PEL):** 1 mg/m<sup>3</sup>

ACGIH Threshold Limit Value (TLV): 1 mg/m<sup>3</sup>

# **EMERGENCY AND FIRST AID PROCEDURES**

Eyes:	Flush with water for 10 minutes. Call a physician.	
Skin:	Wash thoroughly with water.	
Inhalation:	Remove to fresh air or administer oxygen. Call a physician.	
Ingestion:	If patient is fully conscious, give two glasses of water. Obtain medical attention immediately.	

# SECTION V - FIRE AND EXPLOSION HAZARD DATA

Flash Point: Core>140°C

Metal: NA

Flammable Limits: NA

**Extinguishing Media:** Special mixtures of dry chemicals suitable for metal fires such as dry sand, dolomite, graphite, salt, and soda ash.

**Do Not Apply Water to Burning or Melted Metal.** Water can be used to cool containers when no contact with metal will occur.

Auto Ignition Temperature: NA

# SECTION VI - ACCIDENTAL RELEASE MEASURES

**Steps to be taken in case material is spilled:** Protect skin and eyes by wearing safety glasses and gloves. Ventilate the area. Restrict and collect spilled materials

# SECTION VII - HANDLING AND STORAGE

Storage Requirements: Store in low temperature and low humidity area.

**Handling Precautions:** Users should wear protective gloves and glasses when handling solder paste. soldering should be conducted in good ventilation environment.

**Other Precautions:** Keep the tin, silver, and lead fume levels below the OSHA permissible exposure limit.

## **SECTION VIII - CONTROL MEASURES**

Respiratory Protection (TYPE): NIOSH approved. Ventilation: Yes Mechanical (General): Optional Local Exhaust: Yes Eye Protection: Safety glasses Protective Gloves: Rubber gloves Other Protective Clothing or Equipment: Laboratory or worker coat Work/Hygienic Practices: Wash hands after handling the product, wear safety glasses during handling

#### SECTION IX - PHYSICAL AND CHEMICAL CHARACTERISTICS

Boiling Point: NA Specific Gravity (Water = 1): 4.0-5.5 Vapor Pressure (mm Hg): NA Percent Volatile by Volume: NA Vapor Density (Air = 1): NA Evaporation Rate (Butyl Acetate = 1): NA Melting Point: 217°C Solubility in Water: Partial Reactivity in Water: None Appearance and Odor: Pasty and mild solvent odor

## SECTION X - STABILITY AND REACTIVITY

Stability: Product is stable
(Conditions to Avoid): Contact with strong acids and alkali.
Incompatibility: Strong acids and alkali.
Hazardous Decomposition Products: Not determined.
Hazardous Polymerization: Not determined.
(Conditions to Avoid): Not determined

#### SECTION XI - TOXICOLOGICAL INFORMATION

#### **Acute Toxicity Data**

- 1) Oral: LD-50 (rat): Not available
- 2) Inhalation: LC-50 (rat): Not available
- 3) Dermal: LD-50 (rabbit): Not available
- 4) Skin Irritation: (rabbit): Not available

#### **Chronic Toxicity Data**

- 1) Repeated Skin Application: (rat): Not available
- 2) Eye Irritation: (rabbit): Not available

# SECTION XII - ECOLOGICAL INFORMATION

This Material has not been Tested for Environmental Effects.

# SECTION XIII - DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose of in accordance with EPA regulations.

# SECTION XIV- TRANSPORTATION

**D.O.T. Proper Shipping Name:** Non-hazardous **Identification Number:** NA **Type D.O.T Label Required Information:** NA

Hazard Class: NA Packing Group: NA

# SECTION XV - REGULATORY INFORMATION

OSHA Hazardous Chemical According to 29 CFR 1910.1200: None

Carcinogenicity Classification (Components Present at 0.1% or More): Non-Carcinogenic International Agency for Research on Cancer (IARC): Not Listed American Conference of Governmental Industrial Hygienists (ACGIH): Not Listed National Toxicology Program (NTP): Not Listed Occupational Safety and Health Administration (OSHA): Not Listed

None of the Components of this Product are Listed on the U.S. Toxic Substances Control Act. Inventory or Otherwise Comply with TSCA Pre-manufacture Notification Requirements. This Product is RoHS Compliant.

#### **SECTION XVI - OTHER INFORMATION**

The labeling of this product is indicated in Section II. The full text of all abbreviations indicated by codes in the MSDS are as follows:

- S-36/39 Wear suitable protective clothing and eye/face protection
  - H334 May cause allergy or asthma symptoms or breathing difficulties if inhaledH317 May cause an allergic skin reaction
  - P280 Wear protective gloves/protective clothing/eye protection/face protectionP302+P352 IF ON SKIN: Wash with plenty of water and soap.

**Disclaimer:** Judgments as to the suitability of information herein or the purchaser's purposes are necessarily the purchaser's responsibility. Reasonable care has been taken in the preparation of this material, but there are NO WARRANTIES, NO REPRESENTATIONS AND NO RESPONSIBILITY AS TO THE ACCURACY OR THE SUITABILITY OF THIS INFORMATION FOR ANY PURCHASER'S USE OR FOR ANY CONSEQUENCE TO USE.