# SAFETY DATA SHEET SUPERIOR No. 9000-TF

DATE REVISED: November 25, 2019

### **SECTION 1 -- IDENTIFICATION**

Product Name/Part number: Superior No. 9000-TF

**Recommended use:** No-Clean Tacky Flux

Manufacturer: Superior Flux & Mfg. Co. Mfg. Phone No. (440) 349-3000

6615 Parkland Blvd Cleveland OH, 44139

Emergency Phone No.: 1-800-424-9300 (CHEMTREC)

# **SECTION 2 – HAZARD(S) IDENTIFICATION**

### Classification of the substance or mixture

### GHS Classification in accordance with OSHA HCS (29 CFR 1910)

Acute toxicity, Oral (Category 4)
Aspiration toxicant (Category 1)
H302
Aspiration toxicant (Category 1)
H318
Acute aquatic toxicity (Category 1)
H402
Chronic aquatic toxicity (Category 1)
H412

See below for full text of H-Statement

# GHS Label Elements, including precautionary statements

### Pictogram(s):







Signal Word: Danger

### **Hazard Statement(s)**

H302\*\* Harmful if swallowed

H304 May be fatal if swallowed and enters airways.

H318 Causes serious eye damage H402\*\* Harmful to aquatic life.

H412 Harmful to aquatic life with long lasting effects

### **Precautionary statement(s)**

P260 Do no	ot breathe dust,	fumes, vapors,	spray, or mist.
------------	------------------	----------------	-----------------

P264 Wash skin thoroughly after handling

P270 Do not eat, drink, or smoke when using this product.

P273 Avoid release to the environment

P280 Wear protective gloves, face protection, and eye protection

P301+P310+P331 IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do

NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower.

<sup>\*\*</sup>May be omitted from label due to presence of stricter or more severe statement.

P305+P351+P338+P310 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call POISON CENTER or doctor.

P337+P313 If eye irritation persists: Get medical advice or attention

P405 Store locked up

P501 Dispose of contents to an approved waste disposal plant

Hazards not otherwise classified or not covered by GHS: None

### **SECTION 3 – COMPOSITION INFORMATION**

Components	<b>CAS Number</b>	<b>%</b>
Oxylated glycol	25322-69-4	5 - 15
Hydro-treated mid petroleum distillate 64742-46-7		< 5
Hydroxybenzoic acid	69-72-7	< 2
Carboxylic acid	98-98-6	< 2
Proprietary acetate	Proprietary	< 2

### **SECTION 4 – FIRST AID MEASURES**

Description of first aid measures

General advice: Consult a physician. Show this safety data sheet to the doctor in

attendance. Move out of dangerous area.

Inhalation: If breathed in, move to fresh air. If not breathing, give artificial respiration.

Consult a physician.

Eyes: Rinse thoroughly with plenty of water for at least 15 minutes and consult a

physician.

**Skin:** Wash off with soap and plenty of water. Consult a physician.

**Ingestion:** Do NOT induce vomiting. Never give anything by mouth to an unconscious

person. Rinse mouth with water. Consult a physician.

Most Important Symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in section 2 (labeling)

# **SECTION 5 – FIREFIGHTING MEASURES**

Suitable Extinguishing Media: Not applicable

Special Hazards: No data available

Special protective actions for firefighters: Wear self-contained breathing apparatus for

firefighting if necessary.

### SECTION 6 - ACCIDENTAL RELEASE MEASURES

**Personal Precautions and Equipment and emergency procedures:** Use personal protective equipment. Avoid breathing vapors, fumes, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas.

See section 8 for personal protection.

**Environmental Precautions:** Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

In Case Material is spilled: Contain spillage, then collect and place in container for disposal according to local regulations.

### **SECTION 7 - HANDLING AND STORAGE**

**Precautions for safe handling:** Avoid contact with skin and eyes. Avoid inhalation of vapor or mist. Soldering should be conducted in a well ventilated area

For full precaution statements see Section 2

**Storage Requirements:** Store locked up in a low temperature, low humidity, and well ventilated area.

# SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION CONTROL PARAMETERS

OSHA Permissible Exposure Limit (PEL): 20 ppm ACGIH Threshold Limit Value (TLV): 20 ppm

**Engineering Controls:** Use local exhaust ventilation to maintain air concentrations of vapors and fumes below occupational exposure standards.

Special Engineering Control Needs: Not applicable

- **Respiratory Protection:** Where risk assessment shows air-purifying respirators are appropriate, use a face mask as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face face respirator with multi-purpose combination (USA) or ABEK (EN 14387) respirator cartridges. Use respirators and components tested an approved under appropriate government standards such as NIOSH (USA) or CEN (EU).
- **Protective Gloves:** Handle with gloves. (Nitrile Rubber recommended) Gloves must be inspected prior to use. Use proper glove removal techniques (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good lab practices. Wash and dry hands after handling.
- Eye Protection: Use appropriate fitting safety goggles. Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (USA) or EN 166 (EU)
- **Body Protection:** Where risk assessment shows body protection is appropriate, use a worker coat, laboratory coat, or rubber apron. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

### SECTION 9 - PHYSICAL AND CHEMICAL CHARACTERISTICS

**Appearance** Brown paste

**Odor** Mild

**Odor threshold** No data available рH No data available Melting point/Freezing point No data available Initial boiling point and boiling range No data available Flash point Not applicable **Evaporation rate** No data available Flammability (Solid, gas) Not applicable Upper flammability or explosive limits Not applicable Lower flammability or explosive limits Not applicable Vapor pressure Not applicable Vapor density Not applicable **Relative density** No data available Solubility(ies) Insoluble in water Partition coefficient: n-octanol/water No data available **Auto-ignition temperature** Not applicable **Decomposition temperature** No data available Viscosity No data available

### **SECTION 10 - STABILITY AND REACTIVITY**

Reactivity: No data available

**Stability:** Product is stable under recommended storage conditions

Possibility of hazardous reactions: No data available

Conditions to Avoid: Heat, sparks and flames

**Incompatibility:** Oxidizing agents, soluble carbonates, soluble phosphates, hydroxides, metals,

peroxides, permanganates, amines, alcohols and nitric acid

**Hazardous Decomposition Products** Carbon oxides (Under fire conditions)

In the event of fire: See Section 5

### SECTION 11 - TOXICOLOGICAL INFORMATION

Likely Route(s) of Exposure: Inhalation, ingestion, skin and eye contact

**Symptoms (Immediate and Chronic) from** 

Acute Exposure No data available Prolonged or Repeated Exposure No data available

**Measure(s)** of toxicity

No data available

Is this chemical listed in the National Toxicology Program (NTP) Report on Carcinogens?

No data available

Is this chemical found to be a potential carcinogen in the International Agency for

Research on Cancer (IARC) Monographs or by the Occupational Safety and Health Administration (OSHA)?

No data available

### **SECTION 12 - ECOLOGICAL INFORMATION**

**Toxicity** No data available

**Persistence and degradability** No data available

Bioaccumulative potentialNo data availableMobility in soilNo data availableOther adverse effectsNo data available

### **SECTION 13 - DISPOSAL CONSIDERATIONS**

Waste treatment methods

**Product** Offer surplus and non-recyclable solutions to a licensed disposal company.

Contact a licensed professional waste disposal service to dispose of this material.

**Contaminated packaging** Dispose of as unused product.

### **SECTION 14- TRANSPORTATION**

D.O.T. (USA) Not regulated IATA (International) Not regulated

### **SECTION 15 - REGULATORY INFORMATION**

**SARA 302 Components** No Chemicals in this material are subject to the reporting

requirement of SARA Title III, Section 302.

SARA 313 Components This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 302 Components Acute Health Hazard, Chronic Health Hazard

### California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

### **SECTION 16 - OTHER INFORMATION**

#### **Further information:**

Judgments as to the suitability of information herein or the purchaser's purposes are necessarily the purchaser's responsibility. The above information does not represent any guarantee of the properties of the product. It is believed to be correct but does not purport to be all inclusive and should be used only as a guide. Reasonable care has been taken in the preparation of this material and is based on the present state of our knowledge.

Superior Flux & Mfg. Co. shall not be held liable for any damage resulting from handling or from contact with the above product.

### **Preparation information**

Superior Flux & Mfg. Co.

440-349-3000