



# ANTI-BORAX FORGE BORAX



## FORGE WELDING FLUX POWDER

- **Anti-Borax Forge Borax** is a non-metal bearing forge welding flux.
- **Anti-Borax Forge Borax** is ideal for farrier and forge applications.

### DESCRIPTION

**Anti-Borax Forge Borax** is an off-white granular powder. **Anti-Borax Forge Borax** contains no water of hydration and melts smoothly at 741°C/1350°F. The flux promotes deep penetration of the filler metal in the joints, resulting in high bond strength. **Anti-Borax Forge Borax** removes oxides rapidly and thoroughly without bubbling, keeping impurities and porosity out of the joints.

### PHYSICAL PROPERTIES

Form	Granular Powder
Color	Off White
Volatile Content	Less than 0.5%
Fluoride Content	None
Lower Explosion Limit	None
Flash Point	None

**THIS PRODUCT IS RoHS COMPLIANT**

### SAFETY PRECAUTIONS

**Anti-Borax Forge Borax** contains inorganic borates and should be handled with care and the normal precautions taken when working with chemical products.

When working with **Anti-Borax Forge Borax** adequate exhaust ventilation must be present to avoid breathing the fumes that may come from the inorganic borates. Avoid contact with eyes, skin, and mucous membranes. Always wear NIOSH approved safety equipment when working with chemicals. In case of eye contact, flush freely with water and call a physician immediately. Store away from heat, moisture and water.

Refer to Material Safety Data Sheet (MSDS) for additional safety information.

**Anti-Borax Forge Borax** has a two (2) year shelf life.

*Superior manufactures quality fluxes. Our business is solving problems.*

